



Models: mISA (Product Specifications)	500W	1100W	1200W	2100S	2200S	3200S
<b>Deployment Type (Business)</b>	Small	Small, Medium	Medium	Medium, Large	Large	Very Large
Recommended Connected PC	200	300	500	2,000	3,000	4,000
Recommended Corporate Users (Websense)	1000	1000	5,000	10,000	15,000	20,000
<b>System Performance</b>						
Firewall - Throughput (mbps) Max	1800	1800	2000	2400	2400	2600
HTTP - Throughput (mbps) Max	120	120	150	200	200	240
VPN - Throughput (mbps) Max	100	100	160	200	200	200
<b>High Availability, Scalability and Replication</b>						
Scalability: Microsoft Network Load Balancer	No	No	No	No	No	No
High-Availability: Active/Active Failover (NLB)	No	No	No	No	No	No
<b>Hardware Specifications</b>						
<b>Network Ports: LAN PCIe (RJ45)</b>	4-GbE	4-GbE	6-GbE	6-GbE	6-GbE	8-GbE
<b>Network Port: Lights Out Management</b>	Optional, Shared	Optional, Shared	Optional, Shared	Yes, Dedicated	Yes, Dedicated	Yes, Dedicated
<b>Hardware Crypto Accelerator CPU-Off-Load</b>	No, Software Only	No, Software Only	Yes, 64-bit PCI-X	Yes, 64-bit PCIe	Yes, 64-bit PCIe	Yes, 64-bit PCI-X
TPS/Throughput: SSL or IPsec Rating	-	-	7,000 / 1Gbps max	17,000 / 2.5Gbps(max)	17,000 / 2.5Gbps (max)	11,000 / 2.5Gbps (max)
<b>CPU-Qty / Core Type</b>	(1) Intel Pentium Dual	(1) Intel Pentium Dual	(1) Intel Pentium Dual	(1) Xeon Quad	(1) Xeon Quad	(2) Xeon Quad
<b>Memory-RAM</b>	2 GB	2 GB	2 GB	4 GB	4 GB	4 GB
<b>Hard Disk: System OS</b>	(1) 3.5" Internal	(2) 3.5" Internal	(2) 3.5" Internal	(2) 3.5" Hotswap, Front	(2) 3.5" Hotswap, Front	(2) 3.5" Hotswap, Front
<b>LCD Interface w/6-Keypad</b>	No	Yes, Graphical	Yes, Graphical	Yes, Graphical	Yes, Graphical	Yes, Graphical
<b>Power Supply Module</b>	Single	Single	Single	Single	Dual, Hotswap	Dual, Hotswap
<b>Form-Factor</b>	1U 2-Post	1U 2-Post	1U 2-Post	1U 4-Post	1U 4-Post	1U 4-Post
<b>Management: Features by nAppliance</b>						
<b>LCD based Appliance Configuration Manager</b>	Yes	Yes	Yes	Yes	Yes	Yes
<b>ONEface: Web based Appliance Manager</b>						
Web-Based Appliance Setup and Management	Yes	Yes	Yes	Yes	Yes	Yes
<b>FFRS: Flash Based Field Recovery System (CLI)</b>						
Recovery Bare-Metal: Restore to Factory Default	Yes	Yes	Yes	Yes	Yes	Yes
<b>LOM: Lights-Out Remote Appliance Management</b> (It provides BIOS-Level KVM Access over Web even when Appliance is powered-off)						
IPMI based Out of Band Management	Optional, IPMI over LAN	Optional, IPMI over LAN	Optional, IPMI over LAN	Yes, IPMI iKVM over LAN	Yes, IPMI iKVM over LAN	Yes, IPMI iKVM over LAN
<b>Management: Microsoft Built-In Support</b>						
<b>ISA Configuration Management</b>						
Centralized Multi-ISA Management Console (CSS)	No, Only Local	No, Only Local	No, Only Local	No, Only Local	No, Only Local	No, Only Local
<b>System Software</b>						
<b>Appliance System Software:</b>						
Hardened Microsoft Embedded Operating System	Windows Server 2003	Windows Server 2003	Windows Server 2003	Windows Server 2003	Windows Server 2003	Windows Server 2003
<b>Microsoft Security Suite</b>						
ISA: Internet Security & Acceleration Server 2006	Standard-Workgroup	Standard-Workgroup	Standard-Workgroup	Standard Edition	Standard Edition	Standard Edition (2-CPU Lic)
<b>Commerical 3rd Party Applications Support</b>	Yes	Yes	Yes	Yes	Yes	Yes
<b>Pricing (MSRP) - USA</b>						
<b>mISA Appliance: Standard Edition</b>	\$ 2,749	\$ 3,999	\$ 5,395	\$ 8,899	\$ 11,549	\$ 16,699